

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



528047


(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/027214 A1

- (51) International Patent Classification⁷: E21B 47/022, 47/01
- (74) Agent: SCHNEIDER, Michael; Hammonds, Thomas-Wimmer-Ring 17, 80539 München (DE).
- (21) International Application Number: PCT/EP2003/010474
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 19 September 2003 (19.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- (30) Priority Data: 0221717.2 19 September 2002 (19.09.2002) GB
- (71) Applicant (*for all designated States except US*): LAT-TICE INTELLECTUAL PROPERTY LTD [GB/GB]; 1-3 Strand, London WC2N 5EH (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): DIMITROFF, Ted [US/US]; 7850 East Highway AB, Columbia, MO 65201 (US).
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PITCH SENSING IN DRILLING MACHINES



(57) **Abstract:** A pitch sensor tool for a stem boring or drilling machine, for example a sub-surface directional drilling machine having a stem (102) and a drilling head (206). The pitch sensor tool comprises: a generally cylindrical housing (212) adapted to be mechanically coupled to said stem (102) and to said drilling head (206), and a pitch sensing device, the pitch sensing device being disposed in or on the housing (212) and being adapted to transmit a reading of the sensed pitch of the pitch sensor tool. In one example, the pitch sensing device is housed in a compartment (214) in the pitch sensor tool. Also disclosed are a boring or drilling tool incorporating the pitch sensing tool and a drilling head, and a stem boring or drilling machine incorporating the pitch sensing tool. Separation of the pitch sensing device from the rotating parts (i. e. drilling head or guide head) means that the pitch reading can be measured accurately and during a drilling procedure, as well as after it.

WO 2004/027214 A1